

Page 1 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

Safety data sheet
 according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Building material industry:
 mortar, rendering
 Chemical industry:
 neutralisation, pH-adjustment, catalyst
 Environmental protection:
 flue gas treatment, waste water treatment, sludge treatment
 Drinking water treatment:
 pH-value, decarbonisation, softening, hardening

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

SCHAEFER KALK GmbH & Co. KG, Louise-Seher-Strasse 6, 65582 Diez, Germany
 Phone:+49-6432-503-0, Fax:+49-6432-503-269
 info@schaeferkalk.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (SKC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H335-May cause respiratory irritation. H315-Causes skin irritation. H318-Causes serious eye damage.

P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352-IF ON SKIN: Wash with plenty of water and soap. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

P501-Dispose of contents / container in accordance with all local, regional, national and international laws.

Calcium dihydroxide

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Page 2 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Calcium dihydroxide	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475151-45-XXXX
Index	---
EINECS, ELINCS, NLP	215-137-3
CAS	1305-62-0
content %	10-40
Classification according to Regulation (EC) 1272/2008 (CLP)	STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash affected area immediately with plenty of water for 15 to 20 minutes. Take off contaminated clothing.

If applicable, consult doctor if necessary.

Eye contact

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Wash mouth with water and drink copious quantities of water. Do not induce vomiting. Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Eye-rinse bottle

No known delayed effects. Consult a physician for all exposures except for minor instances.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

The product does not burn.

Adapt to the nature and extent of fire.

Extinguishment powder

Foam

CO₂

Unsuitable extinguishing media

None

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

Protective respirator with independent air supply.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.

Ensure sufficient supply of air.

Do not breathe spray.

Avoid contact with skin and eyes.

6.2 Environmental precautions

Contain the spillage.

Avoid uncontrolled spills to watercourses and drains (pH rising).

Inform the competent authorities when water or canalisation has been infiltrated.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Or:

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid aerosol formation.

Avoid contact with skin and eyes.

Page 3 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

Wear protective equipment (see section 8).
 Separate storage of protective clothing.
 Handling systems should preferably be enclosed. When handling container usual precautions should be paid to the risks outlined in the Council Directive 90/269/EEC.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 There should be an eyewash station and safety shower located near the area of use.
 Do not wear contact lenses when handling this product.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.
 Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Keep away from acids, significant quantities of paper, straw, and nitro compounds.
 Keep out of the reach of children.
 Do not use uncoated aluminium for transport or storage.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Calcium dihydroxide		Content %:10-40
WEL-TWA: 5 mg/m ³ (WEL-TWA), 1 mg/m ³ (9) (EU)	WEL-STEL: 4 mg/m ³ (9) (EU)	---	
Monitoring procedures:	ISO 15202 (Determination of metals and metalloids in airborne particulate matter by inductive coupled plasma emission spectrometry) - 2000(Part 1), 2001(Part 2), 2004 (Part 3) DFG (E), DFG (D) (Alkali metal hydroxides and alkali earth hydroxides) - 2001, 1998 - EU project BC/CEN/ENTR/000/2002-16 card 42-2 (2004) OSHA ID-121 (Metal and metalloid particulates in workplace atmospheres) - 2002 - EU project BC/CEN/ENTR/000/2002-16 card 42-4 (2004)		
BMGV: ---	Other information: ---		

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BGMV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Calcium dihydroxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,49	mg/l	
	Environment - soil		PNEC	1080	mg/kg dw	
	Environment - marine		PNEC	0,32	mg/l	
	Environment - sewage treatment plant		PNEC	3	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	4	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	1	mg/m ³	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	4	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m ³	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).
 Face protection (EN 166)
 Do not wear contact lenses when handling this product.

Skin protection - Hand protection:
 Protective nitrile gloves (EN 374)
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

GB

Page 4 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).
 Clothing fully covering skin.
 Full length pants, long sleeved overalls, with close fittings at openings.
 Wear acid-proof, resp. alkali-resistant and dust-tight shoes.

Respiratory protection:
 Normally not necessary.

Thermal hazards:
 If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

8.2.3 Environmental exposure controls
 No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	White
Odour:	Odourless
Odour threshold:	Not determined
pH-value:	12,4 (20°C, saturated solution Ca(OH) ₂)
Melting point/freezing point:	0 °C (water)
Initial boiling point and boiling range:	100 °C (Water)
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not flammable
Upper explosive limit:	Not flammable
Vapour pressure:	2,3 kPa (20°C)
Vapour density (air = 1):	Not determined
Density:	1,06 - 1,38 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	1844,9 (Regulation (EC) 440/2008 A.6. (WATER SOLUBILITY), Calcium dihydroxide)
Partition coefficient (n-octanol/water):	n.a.
Auto-ignition temperature:	Not determined
Decomposition temperature:	580 °C (decomposition to CaO and H ₂ O)
Viscosity:	Not determined
Explosive properties:	Not determined
Oxidising properties:	No
9.2 Other information	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.
 Avoid contact with alkali sensitive materials.
 Avoid contact with strong acids (exothermic reaction possible).

10.2 Chemical stability


Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Exothermic reaction possible with:

Acids

When heated above 580°C, calcium hydroxide decomposes to produce calcium oxide (CaO) and water (H₂O).




10.4 Conditions to avoid

None known


10.5 Incompatible materials

Calcium hydroxide reacts with carbon dioxide to form Calcium carbonate:



Calcium hydroxide reacts with acids to form Calcium salts.

Calcium hydroxide reacts with aluminium and brass in the presence of moisture under formation (or release) of hydrogen gas:



10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Page 6 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							No
12.4. Mobility in soil:							Calcium hydroxide reacts with carbon dioxide to form calcium carbonate, which is sparingly soluble, and so presents a low mobility in most ground.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Calcium dihydroxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	50,6	mg/l			freshwater
12.1. Toxicity to fish:	LC50	96h	457	mg/l			marine water
12.1. Toxicity to daphnia:	EC50	48h	49,1	mg/l			freshwater
12.1. Toxicity to daphnia:	NOEC/NOEL	14d	32	mg/l			marine water
12.1. Toxicity to daphnia:	LC50	96h	158	mg/l			marine water
12.1. Toxicity to algae:	EC50	72h	184,57	mg/l			freshwater
12.1. Toxicity to algae:	NOEC/NOEL	72h	48	mg/l			freshwater
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:							Not relevant for inorganic substances.
12.4. Mobility in soil:							Calcium dihydroxide, which is sparingly soluble, presents a low mobility in most soils.
12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.6. Other adverse effects:							pH-value of > 12 will rapidly decrease as result of dilution and carbonation., Even though this product can be used to neutralise over-acidified water, when 1g/l is exceeded organisms in the water may be affected adversely.
Toxicity to bacteria:							In high concentrations the product provokes an increase in temperature and of the pH-value. It is used to sanitise sewage sludge
Other organisms:	NOEC/NOEL		2000	mg/kg dw			soil macroorganisms
Other organisms:	NOEC/NOEL		12000	mg/kg dw			soil microorganisms
Other organisms:	NOEC/NOEL	21d	1080	mg/kg			terrestrial plants

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

10 13 04 wastes from calcination and hydration of lime

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

For contaminated packing material

Pay attention to local and national official regulations.

Uncontaminated packaging can be recycled.

SECTION 14: Transport information

Page 7 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

General statements

14.1. UN number: 3266

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
 UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CALCIUM DIHYDROXIDE)
 14.3. Transport hazard class(es): 8
 14.4. Packing group: III
 Classification code: C5
 LQ: 5 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: E



Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (CALCIUM DIHYDROXIDE)
 14.3. Transport hazard class(es): 8
 14.4. Packing group: III
 EmS: F-A, S-B
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Corrosive liquid, basic, inorganic, n.o.s. (CALCIUM DIHYDROXIDE)
 14.3. Transport hazard class(es): 8
 14.4. Packing group: III
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freight as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with trade association/occupational health regulations.

Observe Regulation (EU) No 528/2012 concerning the placing of biocidal products on the market.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.
 A chemical safety assessment was carried out for the following substance(s):
 Calcium dihydroxide

SECTION 16: Other information

Revised sections: 8, 11, 12

Link exposure scenarios (Annex as a separate document):

https://sichdatonline.chemical-check.de/Dokumente/714/EX/A-3_0012_20-03-2018_EN_EX.pdf

References

90/269/EWG
 Booklet L64 - Safety Signs and Signals. The Health and Safety (Safety Signs and Signals) Regulation 1996 - Guidance on Regulations (HSE) - ISBN 0 7176 0870 0
 IUCLID Dataset 2000
 Merck Index (Ed. Merck & Co, Rahway, USA)
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
 Skin Irrit. — Skin irritation
 Eye Dam. — Serious eye damage

GB

Page 8 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

Any abbreviations and acronyms used in this document:

AC	Article Categories
acc., acc. to	according, according to
ACGIH	American Conference of Governmental Industrial Hygienists
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL	Acceptable Operator Exposure Level
AOX	Adsorbable organic halogen compounds
approx.	approximately
Art., Art. no.	Article number
ATE	Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM	Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA	Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF	Bioconcentration factor
BGV	Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT	Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV	Biological monitoring guidance value (EH40, UK)
BOD	Biochemical oxygen demand
BSEF	Bromine Science and Environmental Forum
bw	body weight
CAS	Chemical Abstracts Service
CEC	Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level

GB

Page 9 of 9
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.03.2018 / 0012
 Replacing version dated / version: 21.07.2017 / 0011
 Valid from: 20.03.2018
 PDF print date: 10.04.2018
 SCHAEFER PRECAL® - Ca(OH)₂ Suspension in water
 Preparation of calcium hydroxide with water

ODP Ozone Depletion Potential
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PAH polycyclic aromatic hydrocarbon
 PBT persistent, bioaccumulative and toxic
 PC Chemical product category
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 POCP Photochemical ozone creation potential
 ppm parts per million
 PROC Process category
 PTFE Polytetrafluorethylene
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SADT Self-Accelerating Decomposition Temperature
 SAR Structure Activity Relationship
 SU Sector of use
 SVHC Substances of Very High Concern
 Tel. Telephone
 ThOD Theoretical oxygen demand
 TOC Total organic carbon
 TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
 WHO World Health Organization
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.